

Product information | TECHNICAL DATA SHEET

ELECTRICAL APPLIANCE WHITE.

400 ml, 11 Oz, 315 g.

GENERAL DESCRIPTION

Paint composed of high quality hydroxyl acrylic resins that are formulated with titanium dioxide and additives to obtain a perfect, bright finish. Ideal for painting household appliances.

FEATURES

- Very fast drying.
- Good hardening.
- Highly resistant to scratching.
- Excellent adherence.
- Does not contain Lead.
- Good covering power.
- Brightness and colour durability.
- No yellowing.
- Easy to apply and recoating.
- Resistant to UV rays.

APPLICATIONS

- Washing machine paint
- Refrigerator paint
- DIY and gardening repairs
- Extractor fan paint
- Dishwasher paint
- Painted outside ovens and microwave

INSTRUCTIONS FOR USE

- Unplug the appliance before painting.
- Clean, degrease and sand the rust from the surface that is to be painted. After that, apply a white anti rust primer as a base.
- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- Thoroughly clean and degrease the object to be painted. Remove corrosion using a wire brush. On plastics and polyesters apply a anchor layer.
- Apply thin coats for best results, always thin layers is better than one thick, paintable after 10 minutes with the same paint.
- Disconnect the electrical appliance before painting.
- Use in well ventilated areas.
- Request safety data sheets.

PHYSICAL PROPERTIES

Brinder type:	Acrylic
Color:	Characteristic white
Brightness:	>80%
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Total drying (ASTM D-1640 ISO 1517):	20'
Coat thickness (ASTM D-823 ISO 2808):	15 µ/layer
Adherence (ASTM D-3359 ISO 2409):	4B
Theoretical yield (continuous painting):	2 m ²
Thinner:	Butyl Acetate
Product life:	>2 years
Recoating:	After 10'
Painted resistance to heat:	120°C
Application conditions:	T° environment min. 8°C T° surface min. 5-50°C Humidity Max. 85% R.H.P

* Adherence tests were performed on steel.

APPARENCE



LABEL



EX014A0905 Blanco
Electrodoméstico

CAP SYSTEM



PACKAGING

Nominal Capacity: 400 ml
Container heat resistance: <50°C
Propellant: DME

Box (6 units)
205 X 140 X 200 mm.



ATENCIÓN

