

## Product information | TECHNICAL DATA SHEET

### TEXTURED BUMPER PAINT

400 ml, 11 Oz, 318 g.

#### GENERAL DESCRIPTION

Paint formulated with high quality combined nitro resins, with a textured finish especially for bumpers.

#### FEATURES

- Very fast drying.
- Excelente flexibilidad.
- Easy to apply and recoat.
- Good adhesion.
- Lead free.
- High covering power.

#### APPLICATIONS

Its use is recommended for the motor industry and especially for painting bumpers.

- Automotive industry.

#### INSTRUCTIONS FOR USE

- Shake the can vigorously before use, for approximately one minute after hearing the sound of the mixer.
- Apply on clean and dry surfaces.
- About bumper does not need primer.
- Apply thin coats for best results, always thin layers is better than one thick, paintable after 10 minutes with the same paint.
- Disconnect the electrical appliance before painting.
- Use it in well ventilated areas.
- Request safety data sheets.

#### PHYSICAL PROPERTIES

|   |  |
|---|--|
| Binder type:                                | Combined nitro   |
| Color:                                      | Black, grey  |
| Texture:                                    | Medium   |
| Shine 60°:                                  | Mate   |
| Dry to the touch (ASTM D-1640 ISO 1517):    | 10'  |
| Total drying (ASTM D-1640 ISO 1517):        | 20'  |
| Coat thickness (ASTM D-823 ISO 2808):       | 15 µ/capa (2 applications)   |
| Adherence (ASTM D-3359 ISO 2409):           | 4B   |
| Theoretical Coverage (continuous painting): | 2 m <sup>2</sup>   |
| Thinner:                                    | Acetato Butilo   |
| Product life:                               | >2 años  |
| Recoating:                                  | After 10'  |
| Painted resistance to heat:                 | 120°C  |
| Application conditions:                     | T° environment min 8°C<br>T° Surface min 5-50°C<br>Humidity max. 85% R.H.P |

\* Adherence tests were performed on steel.

#### CAUTION



#### APPARENCE



#### LABEL



#### CAP SYSTEM



#### PACKAGING

Nominal capacity 400ml.  
Heat resistance of packaging : <50°C  
Propellant: DME  
VOC's: 655g/L

Box (6 units)  
205 X 140 X 200 mm.

