

## Product information | TECHNICAL DATA SHEET

**CONTACT ADHESIVE.** Highly adhesive. Non-removable.  
400 ml, 10.1 Oz, 288 g

### GENERAL DESCRIPTION

Adhesive resin mixed with aliphatic solvents, with a high adhesive power.

### FEATURES

- Adhesive Contact.
- Immediate adhesion.
- Excellent adhesion.
- Doesn't deteriorate materials.
- Not suitable for applications in vehicle headliner.

### APPLICATIONS

Film forming adhesive with immediate and high adhesion. Especially adapted for different automotive\* applications and DIY. The most suitable materials for bonding are:

- Polyurethane and polyethylene foams
- Fibers
- Cork
- Cardboard
- Paper
- Carpet

\* **Not recommended** for gluing objects to car ceilings. (High temperatures caused by the sun plus the object's weight do not make for a good result)

### INSTRUCTIONS FOR USE

- Before using, shake the aerosol vigorously for approximately one minute after the noise of the mixer starts.
- Apply over clean and dry surfaces. On rusty metallic surfaces: Remove corrosion with a wire brush. In plastics like PS and PP apply first a primer layer. See product's behavior in any plastic surface.
- Hold the aerosol upside down after use to purge the valve. If the nozzle is blocked, replace it with a new one.
- Do not apply on plugged-in electrical equipment and use in well-ventilated areas.
- Ask for MSDS.

### PHYSICAL PROPERTIES

Color:	Transparent yellowish
Hardening:	10-60 minuts
Application temperature:	10-60 °C
Maximum exposure temperature:	40°C
Theoretical yield (pintado contiuono):	2m <sup>2</sup>
Solvent:	Hexano
Product life:	>5 years

\*The adhesion tests were done on PP (EPDM modified). Last reví ew's date: 31/01/2017

### CAUTION



### APPEARANCE



### LABEL



EX014PR0801 Adhesive

### CAP SISTEM



### PACKAGING

Nominal capacity: 400 ml.  
Heat resistance of packaging: <50°C  
Propellant: DME

Box (6 units)  
205 X 140 X 200 mm.

