

Product information | TECHNICAL DATA SHEET

CHROME EFFECT PAINT

400 ml, 10 Oz, 287 g.

GENERAL DESCRIPTION

Very fast drying paint formulated with extremely high quality solvent-based acrylic resins and synthetic metallic pigments.

FEATURES

- Very fast drying.
- Good covering capability.
- Good adhesion.
- Does not contain lead nor other heavy metals.
- Easy to apply and repaint.
- It does not have anti-corrosive properties.
- Great metallic effect.
- High decorative power.
- Not resist rubbing or weather.

INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- Apply to clean, dry surfaces. On rusty metallic surfaces remove rust with a wire-brush and prepare an anti-rust primer if considered necessary. Apply an anchor layer on plastics and polyesters.
- For best results apply in thin layers. Three thin layers are always better than one thick one, and may be repainted within fifteen minutes with the same paint.
- Turn the aerosol upside down to clean out the valve after use. If the nozzle becomes blocked replace it with a new one.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.
- This painting not allow subsequent varnishing, it would lose part its metallic effect.
- Has very little mechanical endurance (because of its nature the pigment is in surface and does not resist rubbing.) We do not advise this paint on surfaces that are to be manipulated, eg doorknobs, railings, etc.

PHYSICAL PROPERTIES

Basse pression:	Acrylic resin solvent
Color:	Copper, Gold, Silver
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Completely dry (ASTM D-1640 ISO 1517):	1 h
Thickness of dry layer (ASTM D-823 ISO 2808):	15 micras/layer
Adherence (ASTM D-3359 ISO 2409):	3 B
Theoretical yield (continuous painting):	3 m ² for 400 ml
Thinner:	Aromatic mixture
Product life:	(Well Stored) 5 years
Condition for application:	Minimum room temperature 8°C Surface temperature 5°C a 50°C Max humidity. 85% R.H.P
Heat resistance of paint:	100°C

* All of the adherence tests have been carried out on iron plates.

220421



APPLICATIONS

Due to the product's features we recommend for painting all kinds of surfaces that they want to impart a metallic effect Cromado. High decorative power and very suitable for artistic and decorative arts.

- DIY
- Decoration
- Christmas decoration
- Plastics
- Retouching of metal components

IMAGE



LABEL



COD. BARRAS/BAR CODE

CAP SYSTEM



Pocket Cap
Fino - Fine

Plata Cromada / Silver
EX014PR0101

Oro Cromado / Gold
EX014PR0102

Cobre Cromado / Copper
EX014PR0103

PACKAGING

Nominal capacity 400 ml.
Heat resistance of packaging: <50°C
Propellant: DME

Box (6 units)
205 X 140 X 200 mm.

